

# Installing the HydroVac Pro

## Required tools:

• 7/16 socket wrench

• Phillips screwdriver



Remove bumpers on the handle with a Phillips screwdriver. Keep the screws to reuse. Slide on the mounting bracket. Attach using the same screws from the bumpers.



Using a 7/16 socket, mount the vacuum tank to the handle with the included bolt, lock washer, and washer. Secure the bottom of the tank using the other included bolt.



Set the solution tank into place, matching up the pegs on the bottom to the holes in the base of the vacuum tank. Secure the solution tank in place with Velcro.



Connect the cable actuator bracket to the vacuum tank mounting bracket. Use a 7/16 socket or wrench and the included bolts and nuts. Ensure the cable is routed along the front of the handle, on the solution tank side.



Place the squeegee assembly onto the rear axle. Connect the vacuum hose from the vacuum tank to the squeegee assembly.



Use a Phillips screwdriver to attach the drip bar with the provided brackets. Connect the solution hose from the brass solution tank valve to the drip bar.



Hook the actuator onto the solution tank valve lever. **NOTE: DO NOT MAKE ANY ADJUSTMENTS TO THE CABLE.**



Plug the power cord from the vacuum tank into the provided outlet.


# Operating the HydroVac Pro



Fill the solution tank with water or solution using a hose or bucket.




Flip the switch on the circuit breaker to turn on power.




Push lever forward to open the solution tank valve and apply solution to the floor.



Squeeze the trigger on the machine to activate the vacuum and floor machine motor. Push the machine forward to scrub the floor. The squeegee will lift up the slurry behind the pad.



For storage, unhook the vacuum hose from the squeegee assembly. Hang the squeegee assembly from the tool holder. **NOTE: ALWAYS EMPTY THE SOLUTION AND VACUUM TANKS BEFORE LOWERING THE MACHINE ON ITS BACK.**



The vacuum tank can be emptied via the tank drain at the bottom. To empty the solution tank, make sure the valve lever is in the closed position, lift the actuator off the valve, and then lift the solution tank up off the vacuum tank and dump.

**Do not leave this unit exposed to harsh weather elements.** Temperatures below freezing may damage components and void the warranty. Store in a temperature-controlled environment when possible. When not possible, flush the system with a non-toxic anti-freeze solution prior to storage.

**Do not drop or otherwise subject this unit to excessive impacts.** This may damage internal components. Component malfunctions due to force are not covered under warranty.

## IMPORTANT INFORMATION



**SQUARE  
SCRUB.**

by  Mytee

# HydroVac Pro

Quick Start Guide



SS HPS 18 | SS HPS 20



Register your new extractor at  
[www.squarescrub.com/warranty-registration](http://www.squarescrub.com/warranty-registration)  
to activate your warranty.

Included in this package:



1. Solution tank
2. Vacuum tank assembly
3. Mounting bracket with solution control lever, cable, and actuator
4. Solution hose
5. Crevice tool
6. Vacuum hose
7. Drip bar
8. Squeegee assembly

Find full manuals for your equipment at  
[www.squarescrub.com/product-manuals-sds/](http://www.squarescrub.com/product-manuals-sds/)



**SQUARE  
SCRUB.**

by  Mytee

196 Co. Rd. 702  
Jonesboro, AR 72405  
800-557-6822  
[www.squarescrub.com](http://www.squarescrub.com)